

LM4SEN100

(a picture to be placed here)

Holon LM2/LM4/LM2H/LM4H Line Monitoring Modules

Technical Specification

(Preliminary information)

Rev. 1.00

Target telephone system	Any system equipped with analogue lines/trunks
Number of lines monitored LM2/LM2H	2
LM4/LM4H	4
Line/Trunk terminals	RJ11
Mode of connection	in serial to an analogue line
Selectable disconnect modes	Reversal Polarity and Drop Out Pulse
Disconnection time slots	0.5S, 1.0S, 1.5S
Busy/Reorder Tones detection	425Hz, 480+680Hz
Busy/Reorder Tones cadences	0.5S/0.5S, 0.25S/0.25S
Session Time Duration limits	15min, 30min, or unlimited
Power supply voltage range LM2/LM4	7-10 VDC
LM2H/LM4H	7-48 VDC
Power consumption	150mA @9VDC
AC/DC adaptor	230VAC~50Hz/9VDC-250-400mA
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Dimensions (Approx.)	66 x 28 x 140 mm (w/h/d)
Nett mass (Approx.)	to be defined

Design and specifications are subject to change without notice.